


Normal Wall, Flexible

Halogen-Free Polyolefin Heat Shrink Tubing **pro-POWER**

**RoHS
Compliant**



Applications

The heat shrink tubing is manufactured with modified radiation cross-linked polyolefin. The specially designed halogen free formulation makes the tubing very flexible and shrink at lower temperature. Suitable for applications where temperature sensitive components protection, e.g. PVC jacketed wire and cable and quick shrinkage is required. It has good mechanical and electrical performances.

Characteristics:

- Halogen Free
- Operating temperature -55°C to +125°C
- Min. shrink temperature 70°C
Full recovery temperature: 120°C
- Shrink Ratio 2:1
- Meets Sony-SS-00259
- Standard Colours: Black, Red, Yellow, White, Blue, Brown

Technical Data:

Property	Test Method	Standard Value
Tensile Strength	ASTM D2671	≥10.4 Mpa
Ultimate Elongation	ASTM D2671	≥200%
Longitudinal Shrinkage	UL 224	±5%
Heat Aging Tensile Strength Ultimate Elongation	158°C, 168hrs	≥7.3 Mpa ≥100%
Heat shock	250°C, 4hrs	No cracking, No dripping
Flammability	FMVSS302	Pass
Dielectric Strength	ASTM D150	≥15 kV/mm
Volume Resistivity	ASTM D2671	≥1x10 ¹⁴ Ωcm
Copper Stability	UL224	Pass
Copper Corrosion	UL224	No corrosion

Product Dimensions:

Size		As supplied		After Recovery	
Inch	mm	Internal diameter (mm)	Wall thickness (mm)	Internal diameter Max(mm)	Wall thickness Nom(mm)
1/16	1.6	1.5 ±0.2	0.2 ±0.05	0.65	0.36 ±0.1
3/32	2.4	2.5 ±0.2	0.2 ±0.05	1	0.45 ±0.1
1/8	3.2	3.5 ±0.2	0.2 ±0.05	1.5	0.45 ±0.1
3/16	4.8	5 ±0.2	0.28 ±0.05	2.3	0.56 ±0.1

Normal Wall, Flexible

Halogen-Free Polyolefin Heat Shrink Tubing **pro-POWER**

Size		As supplied		After Recovery	
Inch	mm	Internal diameter (mm)	Wall thickness (mm)	Internal diameter Max(mm)	Wall thickness Nom(mm)
1/4	6.4	6.5 ±0.2	0.28 ±0.05	3	0.56 ±0.1
3/8	9.5	9.5 ±0.3	0.3 ±0.08	4.5	0.56 ±0.1
1/2	12.7	12.5 ±0.3	0.3 ±0.08	6	0.56 ±0.1
3/4	19	19 ±0.5	0.35 ±0.1	9	0.7 ±0.1
1	25.4	26 ±0.5	0.45 ±0.12	12.5	0.9 ±0.15
1-1/2	38.1	41.5 ±1	0.5 ±0.12	20	1 ±0.15
2	50.8	≥50	0.5 ±0.15	25	1.1 ±0.2

Part Number Table

Description	Reel Length	Part Number	Description	Reel Length	Part Number
Heatshrink Tubing Normal Wall 2:1 Black 1.6mm	100m	13633	Heatshrink Tubing Normal Wall 2:1 Red 19mm	100m	13673
Heatshrink Tubing Normal Wall 2:1 Black 2.4mm	100m	13634	Heatshrink Tubing Normal Wall 2:1 Red 25.4mm	50m	13674
Heatshrink Tubing Normal Wall 2:1 Black 3.2mm	100m	13635	Heatshrink Tubing Normal Wall 2:1 Red 38.1mm	50m	13675
Heatshrink Tubing Normal Wall 2:1 Black 4.8mm	100m	13636	Heatshrink Tubing Normal Wall 2:1 Red 50.8mm	25m	13676
Heatshrink Tubing Normal Wall 2:1 Black 6.4mm	100m	13637	Heatshrink Tubing Normal Wall 2:1 Red 1.6mm	5m	15045
Heatshrink Tubing Normal Wall 2:1 Black 9.5mm	100m	13638	Heatshrink Tubing Normal Wall 2:1 Red 2.4mm	5m	15046
Heatshrink Tubing Normal Wall 2:1 Black 12.7mm	100m	13639	Heatshrink Tubing Normal Wall 2:1 Red 3.2mm	5m	15047
Heatshrink Tubing Normal Wall 2:1 Black 19mm	100m	13640	Heatshrink Tubing Normal Wall 2:1 Red 4.8mm	5m	15048
Heatshrink Tubing Normal Wall 2:1 Black 25.4mm	50m	13641	Heatshrink Tubing Normal Wall 2:1 Red 6.4mm	5m	15049
Heatshrink Tubing Normal Wall 2:1 Black 38.1mm	50m	13642	Heatshrink Tubing Normal Wall 2:1 Red 9.5mm	5m	15050
Heatshrink Tubing Normal Wall 2:1 Black 50.8mm	25m	13643	Heatshrink Tubing Normal Wall 2:1 Red 12.7mm	5m	15051
Heatshrink Tubing Normal Wall 2:1 Black 1.6mm	5m	13644	Heatshrink Tubing Normal Wall 2:1 Red 19mm	5m	15052
Heatshrink Tubing Normal Wall 2:1 Black 2.4mm	5m	13645	Heatshrink Tubing Normal Wall 2:1 Red 25.4mm	5m	15053
Heatshrink Tubing Normal Wall 2:1 Black 3.2mm	5m	13646	Heatshrink Tubing Normal Wall 2:1 Red 38.1mm	5m	15054
Heatshrink Tubing Normal Wall 2:1 Black 4.8mm	5m	13647	Heatshrink Tubing Normal Wall 2:1 Red 50.8mm	5m	15055
Heatshrink Tubing Normal Wall 2:1 Black 6.4mm	5m	13648	Heatshrink Tubing Normal Wall 2:1 Yellow 2.4mm	100m	13678
Heatshrink Tubing Normal Wall 2:1 Black 9.5mm	5m	13649	Heatshrink Tubing Normal Wall 2:1 Yellow 3.2mm	100m	13679
Heatshrink Tubing Normal Wall 2:1 Black 12.7mm	5m	13650	Heatshrink Tubing Normal Wall 2:1 Yellow 4.8mm	100m	13680
Heatshrink Tubing Normal Wall 2:1 Black 19mm	5m	13651	Heatshrink Tubing Normal Wall 2:1 Yellow 6.4mm	100m	13681
Heatshrink Tubing Normal Wall 2:1 Black 25.4mm	5m	13652	Heatshrink Tubing Normal Wall 2:1 Yellow 9.5mm	100m	13682
Heatshrink Tubing Normal Wall 2:1 Black 38.1mm	5m	13653	Heatshrink Tubing Normal Wall 2:1 Yellow 12.7mm	100m	13683
Heatshrink Tubing Normal Wall 2:1 Black 50.8mm	5m	13654	Heatshrink Tubing Normal Wall 2:1 Yellow 19mm	100m	13684
Heatshrink Tubing Normal Wall 2:1 Red 1.6mm	100m	13666	Heatshrink Tubing Normal Wall 2:1 Yellow 25.4mm	50m	13685
Heatshrink Tubing Normal Wall 2:1 Red 2.4mm	100m	13667	Heatshrink Tubing Normal Wall 2:1 Yellow 38.1mm	50m	13686
Heatshrink Tubing Normal Wall 2:1 Red 3.2mm	100m	13668	Heatshrink Tubing Normal Wall 2:1 Yellow 50.8mm	25m	13687
Heatshrink Tubing Normal Wall 2:1 Red 4.8mm	100m	13669	Heatshrink Tubing Normal Wall 2:1 Yellow 1.6mm	5m	15056
Heatshrink Tubing Normal Wall 2:1 Red 6.4mm	100m	13670	Heatshrink Tubing Normal Wall 2:1 Yellow 2.4mm	5m	15057
Heatshrink Tubing Normal Wall 2:1 Red 9.5mm	100m	13671	Heatshrink Tubing Normal Wall 2:1 Yellow 3.2mm	5m	15058
Heatshrink Tubing Normal Wall 2:1 Red 12.7mm	100m	13672	Heatshrink Tubing Normal Wall 2:1 Yellow 4.8mm	5m	15059

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

pro-POWER

Normal Wall, Flexible

Halogen-Free Polyolefin Heat Shrink Tubing **pro-POWER**

Description	Reel Length	Part Number
Heatshrink Tubing Normal Wall 2:1 Yellow 6.4mm	5m	15060
Heatshrink Tubing Normal Wall 2:1 Yellow 9.5mm	5m	15061
Heatshrink Tubing Normal Wall 2:1 Yellow 12.7mm	5m	15062
Heatshrink Tubing Normal Wall 2:1 Yellow 19mm	5m	15063
Heatshrink Tubing Normal Wall 2:1 Yellow 25.4mm	5m	15064
Heatshrink Tubing Normal Wall 2:1 Yellow 38.1mm	5m	15065
Heatshrink Tubing Normal Wall 2:1 Yellow 50.8mm	5m	15066
Heatshrink Tubing Normal Wall 2:1 White 1.6mm	100m	13688
Heatshrink Tubing Normal Wall 2:1 White 2.4mm	100m	13689
Heatshrink Tubing Normal Wall 2:1 White 3.2mm	100m	13690
Heatshrink Tubing Normal Wall 2:1 White 4.8mm	100m	13691
Heatshrink Tubing Normal Wall 2:1 White 6.4mm	100m	13692
Heatshrink Tubing Normal Wall 2:1 White 9.5mm	100m	13693
Heatshrink Tubing Normal Wall 2:1 White 12.7mm	100m	13694
Heatshrink Tubing Normal Wall 2:1 White 19mm	100m	13695
Heatshrink Tubing Normal Wall 2:1 White 25.4mm	50m	13696
Heatshrink Tubing Normal Wall 2:1 White 38.1mm	50m	13697
Heatshrink Tubing Normal Wall 2:1 White 50.8mm	25m	13698
Heatshrink Tubing Normal Wall 2:1 White 1.6mm	5m	15067
Heatshrink Tubing Normal Wall 2:1 White 2.4mm	5m	15068
Heatshrink Tubing Normal Wall 2:1 White 3.2mm	5m	15069
Heatshrink Tubing Normal Wall 2:1 White 4.8mm	5m	15070
Heatshrink Tubing Normal Wall 2:1 White 6.4mm	5m	15071
Heatshrink Tubing Normal Wall 2:1 White 9.5mm	5m	15072
Heatshrink Tubing Normal Wall 2:1 White 12.7mm	5m	15073
Heatshrink Tubing Normal Wall 2:1 White 19mm	5m	15074
Heatshrink Tubing Normal Wall 2:1 White 25.4mm	5m	15075
Heatshrink Tubing Normal Wall 2:1 White 38.1mm	5m	15076
Heatshrink Tubing Normal Wall 2:1 White 50.8mm	5m	15077
Heatshrink Tubing Normal Wall 2:1 Blue 1.6mm	100m	13699
Heatshrink Tubing Normal Wall 2:1 Blue 2.4mm	100m	13700
Heatshrink Tubing Normal Wall 2:1 Blue 3.2mm	100m	13701
Heatshrink Tubing Normal Wall 2:1 Blue 4.8mm	100m	13702
Heatshrink Tubing Normal Wall 2:1 Blue 6.4mm	100m	13703
Heatshrink Tubing Normal Wall 2:1 Blue 9.5mm	100m	13704
Heatshrink Tubing Normal Wall 2:1 Blue 12.7mm	100m	13705
Heatshrink Tubing Normal Wall 2:1 Blue 19mm	100m	13706

Description	Reel Length	Part Number
Heatshrink Tubing Normal Wall 2:1 Blue 25.4mm	50m	13707
Heatshrink Tubing Normal Wall 2:1 Blue 38.1mm	50m	13708
Heatshrink Tubing Normal Wall 2:1 Blue 50.8mm	25m	13709
Heatshrink Tubing Normal Wall 2:1 Blue 1.6mm	5m	15078
Heatshrink Tubing Normal Wall 2:1 Blue 2.4mm	5m	15079
Heatshrink Tubing Normal Wall 2:1 Blue 3.2mm	5m	15080
Heatshrink Tubing Normal Wall 2:1 Blue 4.8mm	5m	15081
Heatshrink Tubing Normal Wall 2:1 Blue 6.4mm	5m	15082
Heatshrink Tubing Normal Wall 2:1 Blue 9.5mm	5m	15083
Heatshrink Tubing Normal Wall 2:1 Blue 12.7mm	5m	15084
Heatshrink Tubing Normal Wall 2:1 Blue 19mm	5m	15085
Heatshrink Tubing Normal Wall 2:1 Blue 25.4mm	5m	15086
Heatshrink Tubing Normal Wall 2:1 Blue 38.1mm	5m	15087
Heatshrink Tubing Normal Wall 2:1 Blue 50.8mm	5m	15088
Heatshrink Tubing Normal Wall 2:1 Brown 1.6mm	100m	13721
Heatshrink Tubing Normal Wall 2:1 Brown 2.4mm	100m	13722
Heatshrink Tubing Normal Wall 2:1 Brown 3.2mm	100m	13723
Heatshrink Tubing Normal Wall 2:1 Brown 4.8mm	100m	13724
Heatshrink Tubing Normal Wall 2:1 Brown 6.4mm	100m	13725
Heatshrink Tubing Normal Wall 2:1 Brown 9.5mm	100m	13726
Heatshrink Tubing Normal Wall 2:1 Brown 12.7mm	100m	13727
Heatshrink Tubing Normal Wall 2:1 Brown 19mm	100m	13728
Heatshrink Tubing Normal Wall 2:1 Brown 25.4mm	50m	13729
Heatshrink Tubing Normal Wall 2:1 Brown 38.1mm	50m	13730
Heatshrink Tubing Normal Wall 2:1 Brown 50.8mm	25m	13731
Heatshrink Tubing Normal Wall 2:1 Brown 1.6mm	5m	15100
Heatshrink Tubing Normal Wall 2:1 Brown 2.4mm	5m	15101
Heatshrink Tubing Normal Wall 2:1 Brown 3.2mm	5m	15102
Heatshrink Tubing Normal Wall 2:1 Brown 4.8mm	5m	15103
Heatshrink Tubing Normal Wall 2:1 Brown 6.4mm	5m	15104
Heatshrink Tubing Normal Wall 2:1 Brown 9.5mm	5m	15105
Heatshrink Tubing Normal Wall 2:1 Brown 12.7mm	5m	15106
Heatshrink Tubing Normal Wall 2:1 Brown 19mm	5m	15107
Heatshrink Tubing Normal Wall 2:1 Brown 25.4mm	5m	15108
Heatshrink Tubing Normal Wall 2:1 Brown 38.1mm	5m	15109
Heatshrink Tubing Normal Wall 2:1 Brown 50.8mm	5m	15110

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.