

BBP®11 Small Core Label Rolls

www.BradyID.com/bbp11


BBP®11 1" Small Core:

B-7642 PermaSleeve® HX Polyolefin Wire Marking Sleeves

B-7642 PermaSleeve® HX Polyolefin Wire Marking Sleeves are 2:1 heat shrinkable wire marking sleeves. The sleeves are high-temperature rated, highly flame retardant, and very flexible.

These heat shrinkable wire marking sleeves meet the following industry specifications:

- SAE-AMS-DTL-23053/5 Class 1 & 3
 - SAE-AS-81531
 - MIL-STD-202
 - RoHS compliant
- Tested per:**
 - ASTM E162
 - ASTM E662



! Understanding PermaSleeve Parts:

Example:

HX - 187 - 2 - WT - SC 4

Product Diameter Width Color* Small Core for BBP11 Pieces** (Optional)

Catalog	Sleeves Per Roll	Pieces Per Roll	Approx. Wire Gauge	Range of Wire Dia. Inch (mm) Min. Max.	Supplied Dia. Inch (mm)	Recovered Diameter Inch (mm)	Recovered Wall Thickness Inch (mm)	Sleeve Width Inch (mm)	Rec. Printer	Rec. Ribbon
Single-Sided Printable, 2" Width, BBP11 1" Small Core										
HX-094-2-WT-SC	500	500	24 to 20	0.047 (1.2) - 0.080 (2.0)	0.094 (2.4)	0.047 (1.2)	0.020 (0.5) ± 0.003 (0.07)	2.000 (50.8)	BBP11	R4313/ R6613
HX-125-2-WT-SC	500	500	20 to 16	0.062 (1.6) - 0.110 (2.8)	0.125 (3.2)	0.063 (1.6)	0.020 (0.5) ± 0.003 (0.07)	2.000 (50.8)	BBP11	R4313/ R6613
HX-187-2-WT-SC	500	500	16 to 10	0.094 (2.4) - 0.151 (3.8)	0.187 (4.8)	0.094 (2.4)	0.020 (0.5) ± 0.003 (0.07)	2.000 (50.8)	BBP11	R4313/ R6613
HX-250-2-WT-SC	500	500	12 to 8	0.125 (3.2) - 0.215 (5.5)	0.250 (6.4)	0.126 (3.2)	0.025 (0.6) ± 0.003 (0.07)	2.000 (50.8)	BBP11	R4313/ R6613
HX-375-2-WT-SC	250	250	8 to 4	0.188 (4.8) - 0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	0.025 (0.6) ± 0.003 (0.07)	2.000 (50.8)	BBP11	R4313/ R6613
HX-500-2-WT-SC	250	250	6 to 1	0.250 (6.4) - 0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	0.025 (0.6) ± 0.003 (0.07)	2.000 (50.8)	BBP11	R4313/ R6613
HX-750-2-WT-SC	150	150	2 to 4/0	0.375 (9.5) - 0.700 (17.8)	0.750 (19.0)	0.374 (9.5)	0.030 (0.8) ± 0.003 (0.07)	2.000 (50.8)	BBP11	R4313/ R6613
HX-1000-2-WT-SC	150	150	2/0 to 0.950" dia.	0.450 (12.7) - 0.950 (24.1)	1.000 (25.4)	0.500 (12.7)	0.035 (0.9) ± 0.005 (0.1)	2.000 (50.8)	BBP11	R4313/ R6613
Double-Sided Printable, 2" Width, BBP11 1" Small Core										
2HX-094-2-WT-SC	500	500	24 to 20	0.047 (1.2) - 0.080 (2.0)	0.094 (2.4)	0.047 (1.2)	0.020 (0.5) ± 0.003 (0.07)	2.000 (50.8)	BBP11	R4313/ R6613
2HX-125-2-WT-SC	500	500	20 to 16	0.062 (1.6) - 0.110 (2.8)	0.125 (3.2)	0.063 (1.6)	0.020 (0.5) ± 0.003 (0.07)	2.000 (50.8)	BBP11	R4313/ R6613
2HX-187-2-WT-SC	500	500	16 to 10	0.094 (2.4) - 0.151 (3.8)	0.187 (4.8)	0.094 (2.4)	0.020 (0.5) ± 0.003 (0.07)	2.000 (50.8)	BBP11	R4313/ R6613
2HX-250-2-WT-SC	500	500	12 to 8	0.125 (3.2) - 0.215 (5.5)	0.250 (6.4)	0.126 (3.2)	0.025 (0.6) ± 0.003 (0.07)	2.000 (50.8)	BBP11	R4313/ R6613
2HX-375-2-WT-SC	250	250	8 to 4	0.188 (4.8) - 0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	0.025 (0.6) ± 0.003 (0.07)	2.000 (50.8)	BBP11	R4313/ R6613
2HX-500-2-WT-SC	250	250	6 to 1	0.250 (6.4) - 0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	0.025 (0.6) ± 0.003 (0.07)	2.000 (50.8)	BBP11	R4313/ R6613
2HX-750-2-WT-SC	150	150	2 to 4/0	0.375 (9.5) - 0.700 (17.8)	0.750 (19.0)	0.374 (9.5)	0.030 (0.8) ± 0.003 (0.07)	2.000 (50.8)	BBP11	R4313/ R6613
2HX-1000-2-WT-SC	150	150	2/0 to 0.950" dia.	0.500 (12.7) - 0.950 (24.1)	1.000 (25.4)	0.500 (12.7)	0.035 (0.9) ± 0.005 (0.1)	2.000 (50.8)	BBP11	R4313/ R6613

*Choosing Your PermaSleeve Color	
Standard Stock Colors: WT = White	Special Order Colors: (Contact Brady Customer Service for availability) BK = Black GR = Green RD = Red BL = Blue GY = Gray VT = Violet OR = Orange

** Choosing Your PermaSleeve Pieces (optional):	
While 1 marker per sleeve is standard, you may special order to have each sleeve slit multiple times to produce multiple pieces. Example: HX-187-2-WT-SC becomes HX-187-2-WT-SC-4 This "4" means that this 2.000" sleeve is slit into four 0.500" pieces.	
Standard Option: 1 marker per sleeve	Other Available Slit Options: (Contact Brady Customer Service for availability) 2, 3 or 4 markers per sleeve

See all BBP®11 print ribbon parts on page 152.
Full material descriptions on pages 164-170.

Approx. wire gauge based on AWG for THHN wire.