

Device Information

CA3290

[Printer Friendly Version](#)

BiMOS Dual Voltage Comparators with MOSFET Input, Bipolar Output

[DS Datasheet & Related Docs](#) [Description](#) [Key Features](#) [PT Parametric Data](#)

Ordering Information

Part No.	Status	Temp.	Package
CA3290E	InActive	Mil	8 Ld PDIP

The price listed is the manufacturer's suggested retail price for quantities between 100 and 999 units. However, prices in today's market are fluid and may change without notice.

MSL = Moisture Sensivity Level - per IPC/JEDEC J-STD-020

SMD = Standard Microcircuit Drawing

Description

The CA3290A and CA3290 types consist of a dual voltage comparator on a single monolithic chip. The common mode input voltage range includes ground even when operated from a single supply. The low supply current drain makes these comparators suitable for battery operation; their extremely low input currents allow their use in applications that employ sensors with extremely high source impedances. Package options are shown in the table below.

Key Features

- MOSFET Input Stage
 - Very High Input Impedance (Z_{IN}) 1.7T Ω (Typ)
 - Very Low Input Current at $V_+ = 5V$ 3.5pA (Typ)
 - Wide Common Mode Input Voltage Range (V_{ICR}) Can Be Swung 1.5V (Typ) Below Negative Supply Voltage Rail
 - Virtually Eliminates Errors Due to Flow of Input Currents
- Output Voltage Compatible with TTL, DTL, ECL, MOS, and CMOS Logic Systems in Most Applications

Related Documentation

- [DS](#) Datasheet(s):
- [BiMOS Dual Voltage Comparators with MOSFET Input, Bipolar Output](#)

PT Parametric Data

Key Spec.	Response Time = 500ns
I_{CC} (mA)	1.35
V_{CC} Range ($\pm V$)	2.5 to 15

Applications

- High Source Impedance Voltage Comparators
- Long Time Delay Circuits
- Square Wave Generators
- A/D Converters
- Window Comparators

[About Us](#) | [Careers](#) | [Contact Us](#) | [Investors](#) | [Legal](#) | [Privacy](#) | [Site Map](#) | [Subscribe](#) | [Intranet](#)



©2005. All rights reserved.