



[View RoHS Compliant Devices](#)

SN74F125, Status: ACTIVE
Quadruple Bus Buffer Gate With 3-State Outputs

[Add to my.TI](#)

Features	Samples	Technical Documents
Quality & Pb-Free Data	Pricing/Packaging	Applications Notes
Related Products	Inventory	Simulation Models
Tools & Software	Symbols/Footprints	Reference Designs

Refine Your Selection

- [Logic: Non-Inverting Buffers and Drivers](#)

Support

- [KnowledgeBase](#)
- [Contact Technical Support](#)
- [TI Cross Reference](#)
- [Training](#)
- [Part Marking Lookup](#)
- [Part Number Nomenclature](#)

Datasheet



Quadruple Bus Buffer Gate With 3-State Outputs (Rev. B) (sn74f125.pdf, 302 KB)
 03 Jul 2002 [Download](#)

	SN74F125
Voltage Nodes(V)	5
Vcc range(V)	4.5 to 5.5
Logic	True
Input Level	TTL
Output Level	TTL
Output Drive(mA)	-15/64
No. of Outputs	4
tpd max(ns)	8
Static Current	32
	Samples
	Inventory

Product Information

[Features](#)

[Save this to your personal library](#) |
 [Add to my.TI](#)

- 3-State Outputs Drive Bus Lines or Buffer Memory Address Registers

[Description](#)

The SN74F125 features independent line drivers with 3-state outputs. Each output is disabled when the associated output-