


VERTICAL DEFLECTION CIRCUIT


- RAMP GENERATOR
- INDEPENDENT AMPLITUDE ADJUSTEMENT
- BUFFER STAGE
- POWER AMPLIFIER
- FLYBACK GENERATOR
- INTERNAL REFERENCE VOLTAGE
- THERMAL PROTECTION



SIP10
(Plastic Package)

ORDER CODE : TDA1771

PIN CONNECTIONS (top view)




L771-01.EPS

DESCRIPTION

The TDA1771 is a monolithic integrated circuit in SIP10 package.

It is a full performance and very efficient vertical deflection circuit intended for direct drive of a TV picture tube in Color and B & W television as well as in Monitor and Data displays.

BLOCK DIAGRAM



771-02.EPS

ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
V_S	Supply Voltage	30	V
V_1, V_2	Flyback Peak Voltage	65	V
V_3	Trigger Input Voltage	20	V
V_8	Amplifier Input Voltage	GND to V_S	V
I_O	Output Peak to Peak Current (non repetitive $t = 2\text{ms}$)	6	A
I_O	Output Peak to Peak Current $t > 10\mu\text{s}$	4	A
I_{10}	Pin 10 DC Current at $V_1 < V_9$	100	mA
I_{10}	Pin 10 Peak to Peak Current @ $t_{ly} < 1.5\text{ms}$	3	A
P_{tot}	Total Power Dissipation @ $T_{tab} = 60^\circ\text{C}$	9	W
T_S, T_J	Storage and Junction Temperature	- 40, + 150	$^\circ\text{C}$

1771-01.TBL

THERMAL DATA

Symbol	Parameter	Value	Unit
$R_{th(j-tab)}$	Thermal Resistance Junction-tab Max.	10	$^\circ\text{C/W}$
$R_{th(j-a)}$	Thermal Resistance Junction-ambient Max.	70	$^\circ\text{C/W}$

1771-02.TBL

ELECTRICAL CHARACTERISTICS ($T_{amb} = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
DC ($V_S = 30\text{V}$)						
I_2	Pin 2 Quiescent Current	$I_1 = 0, I_{10} = 0$		16	36	mA
I_9	Pin 9 Quiescent Current	$I_1 = 0, I_{10} = 0$		15	30	mA
$-I_6$	Ramp Generator Bias Current	$V_6 = 0$			0.5	μA
$-I_6$	Ramp Generator Current	$V_6 = 0, -I_4 = 20\mu\text{A}$	18.5	20	21.5	μA
dI_6/I_6	Ramp Gener. Linearity	$V_6 = 0$ to $15\text{V}, -I_4 = 20\mu\text{A}$		0.2	1	%
V_1	Quiescent Output Voltage	$R_a = 30\text{k}\Omega, R_b = 10\text{k}\Omega, V_S = 30\text{V}$	17.0	17.8	18.6	V
		$R_a = 6.8\text{k}\Omega, R_b = 10\text{k}\Omega, V_S = 15\text{V}$	7.2	7.5	7.8	V
V_{1L}	Out Saturation Voltage to GND	$I_1 = 0.5\text{A}$		0.5	1	V
		$I_1 = 1.2\text{A}$		1	1.4	V
V_{1H}	Out Saturation Voltage to V_S	$-I_1 = 0.5\text{A}$		1.1	1.6	V
		$-I_1 = 1.2\text{A}$		1.6	2.2	V
V_4	Reference Voltage	$-I_4 = 20\mu\text{A}$	6.3	6.6	6.9	V
dV_4/V_S	Reference Voltage Drift Versus V_S	$V_S = 10\text{V}$ to 30V		1	2	mV/V
dV_4/dI_4	Reference Voltage Drift Versus I_4	$I_4 = 10\mu\text{A}$ to $30\mu\text{A}$		1.5	2	mV/ μA
V_r	Internal Ref. Voltage		4.26	4.40	4.54	V
G_v	Output Stage Open Loop Gain	$f = 100\text{Hz}$		60		dB
V_{fs}	$V_9 - I_0$ Saturation Voltage	$-I_{10} = 1.2\text{A}$		1.5	2.5	V
V_{10}	Pin 10 Scanning Voltage	$I_{10} = 20\text{mA}$		1.7	3	V
V_3	Trigger Input Threshold	(see note 1)	2.6	3.0	3.4	V
I_3	Trigger Input Bias Current	$V_{IN} = V_3 - 0.2\text{V}$			30	μA
t_3	Trigger Input Width	(see note 2)	20	60	th	μs

1771-03.TBL


Notes : 1. The trigger input circuit can accept, with a metal option, positive and negative going input pulses.

2. $th = \frac{1.2 \cdot t_s}{V_{PP}}$ where t_s is the vertical period and V_{PP} is ramp amplitude at Pin 6

ELECTRICAL CHARACTERISTICS ($T_{amb} = 25^{\circ}\text{C}$ unless otherwise specified) (continued)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
DC ($V_S = 24\text{V}$)						
V_S	Operating Supply Voltage Range		10		30	V
I_1	Peak-to-peak Operating Current Range		0.4		2.5	A
I_S	Supply Current	$I_Y = 2.4\text{A}_{pp}$		315		mA
V_1	Flyback Voltage	$I_Y = 2.4\text{A}_{pp}$		51		V
V_7	Sawtooth Pedestall Voltage			1.85		V
T_{JS}	Junction Temp. for Thermal Shutdown			145		$^{\circ}\text{C}$


1771-04.TBL

APPLICATION CIRCUIT

1771-03.EPS

PACKAGE MECHANICAL DATA

10 PINS - PLASTIC SIP



PM-SIP10.EPS

Dimensions	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A			7.1			0.280
a1	2.7		3	0.106		0.118
B			24.8			0.976
b1		0.5			0.020	
b3	0.85		1.6	0.033		0.063
C		3.3			0.130	
c1		0.43			0.017	
c2		1.32			0.052	
D			23.7			0.933
d1		14.5			0.571	
e		2.54			0.100	
e3		22.86			0.900	
L	3.1			0.122		
L1		3			0.118	
L2		17.6			0.693	
L3			0.25			0.010
M		3.2			0.126	
N		1			0.039	

SIP10.TBL

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No licence is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics - All Rights Reserved

Purchase of I²C Components of SGS-THOMSON Microelectronics, conveys a license under the Philips I²C Patent. Rights to use these components in a I²C system, is granted provided that the system conforms to the I²C Standard Specifications as defined by Philips.

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - China - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco
The Netherlands - Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A.